



FSK-NRZ MHz Khz >>>>

GSL 28A



Power To Communicate



4 Lines Alphanumeric Pager

FEATURE

Large Display For Easy-to-Read

High contrast display of 20 characters X 4 lines alphanumeric.

Wide Range Of Color Casing

Colorful casings are available.

Message Back Up Function


Large Memory Capacity

Huge memory size for 60 private messages, 16 public messages (Motorola's format) or 100 extended public messages (mail drop) with total 24,000 alphanumeric characters; Maximum 30 protected private messages with maximum 12,000 characters.

FUNCTION

- Up to 4 paging addresses
- High-visibility backlight
- Real time clock with alarm function
- Repeated message indication
- Unread message reminder
- Out of range indication
- Error message indication
- Selectable tone and vibration alert mode

DISPLAY



1. In range sign 2. Battery low 3. Buzzer alert

GENERAL GUIDE



SPECIFICATION

Signal Format	POCSAG
Radio Frequency	136MHz – 174MHz 275MHz – 285MHz 416MHz – 420MHz 452MHz – 464MHz
Bit Rate	512bps / 1200bps
Paging Sensitivity	512bps : 19dB μ V/m 1200bps : 22dB μ V/m
Spurious Rejection	>50dB
Channel Spacing	25KHz
Digital Modulation System	FSK
Deviation	+/- 4.5KHz
Intermodulation	>50dB
Battery	One AAA Battery
Battery Life	>30 days
Dimensions	L77 X W53 X H20.5(mm)
Weight (with battery)	65g



Certificate No. : 943540

Group Sense Ltd.
27/F., Wu Chung House, 213 Queen's Road East,
Wanchai, Hong Kong.
Tel. : (852) 2832 8228
Fax. : (852) 2892 0361
Web Site : <http://www.gsl.com.hk>
Email : gsl@gsl.com.hk

TELCOM
RADIOCOMUNICACIONES

AVDA. DE LA INDUSTRIA, 32
28108 - MADRID