

Power Verter DDI 12-12 072

voltage converter

from 

The unit has the following key benefits:

- ? Quick and easy to connect
- ? Power rating to 072W continuous (96W intermittent)
- ? Cool running switch mode design with efficiency typically 80%
- ? Internal protection against over current, transients and overheating.
- ? No quibble warranty



Characteristics	
Input Voltage Range	12Vdc nominal (8-15V)
Output Voltage	13.6Vdc +/- 10%
Continuous Current Rating	13.6V output rated at 6A continuous
Intermittent Current Rating	13.6V output 8A taken for a maximum of 2 minutes followed by 8 minutes rest.
Transient Voltage Protection	Meets ISO7637-2 International Standard for 24Vdc Commercial Vehicles.
Electro Static Voltage Protection	Meets ISO10605, ISO14892, >8kV contact, 15kV discharge.
Output Noise	<50mV pk-pk at continuous load. Meets CISPR25 and VDE0879-3..
Off load current (quiescent current)	<100mA. If connected to the battery, but not powering any equipment.
Power Conversion Efficiency	Typically 80%
Isolation	>400Vrms between input, output and case
Operating Temperature	-25°C to +30°C. +30°C to +8 de-rate linearly to 0A
Storage Temperature	-25°C to +100°C
Operating Humidity	95% non-condensing.
Case Work	Anodized Aluminum, Dust, water and impact resistance IP533
Connections	4 off 6.3mm push on crimp connectors
Weight and Dimensions	Weight: 835g Dimensions 217 (L) x 87 (W) x 50 (H) mm
Mounting Method	"Click 'n' Fit" mounting clip, fitted separately using three hole fixing
Safe Area Protection:	
? Over Current	Limited by current sensing circuit
? Over Heat	Limited by temperature sensing circuit
? Transients	Protected by filters and rugged component selection
? Catastrophic failure	Protected by input fuses
Approvals	89/336/EEC The General EMC Directive 95/54/EC The Automotive EMC Directive (pending) 93/68/EEC The CE Marking Directive
Tested to	ISO7637, ISO10605, ISO11451, ISO11452, CISPR 25, VDE0879-3, EN60945
Markings	CE marked and e marked



AlfaTronix Limited 29 Newtown Business Park, Poole, Dorset BH12 3LL Great Britain
Telephone: +44 (0) 1202 715517. Fax: +44 (0) 1202 715122.
E-mail: sales@alfatronix.ltd.uk. Website: <http://www.alfatronix.ltd.uk>. An ISO9001 Registered Company

TELCOM

www.telcomsa.es

Tel. (+34) 91 103 30 00